

ARM-880RC

Order no.: 0173810

PRODUCT INFORMATION

Audio Matrix System
The system ARM-880... from MONACOR is a highly flexible PA solution for multi-room applications. It is ideally suited for applications in hotels, in restaurants and bars, in conference rooms, schools, sports facilities and fitness centres. Eight different audio sources, e.g. CD players, SAT receivers, radio programmes can be distributed to 8 output zones, assignment as required.
The audio matrix router ARM-880 is the centrepiece of the system. For operation, one amplifier is required for each output used. This may be an individual power amplifier or an active speaker system. Matching wall modules ARM-880WP1, ARM-880WP2 and ARM-880WP3 for remote control of ARM-880 or with additional local inputs for the respective zone are available at option.
With a master/slave connection, it is possible to extend the system to up to 32 output zones.
Connections for various alarm signals and a local microphone are available.
Announcements can be made via 2 optional zone paging microphones ARM-880RC with zone selection.

PA zone paging microphone,
for audio matrix router ARM-880.

- 8 zones
- Zones can individually be controlled, group call
- Replaceable label for marking the zones
- Plug-in electret gooseneck microphone (3-pole XLR)

- 2-tone or 4-tone chime, can be switched off
- Volume control for microphone and chime
- LEDs for indicating operation, output level and selected zone
- 8 additional zones with each extension module (available at option), 32 zones in total with a maximum of 3 extension modules, connection via available flat cable
- Connection to ARM-880 via RJ45 jack and Cat. 5 network cable (supplied w/o cable)
- Power is provided via enclosed power supply

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices

Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).
Do not operate the appliance if there is visible damage to the appliance, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialised workshop for repair.
If the appliance is to be taken out of service permanently, hand it over to a local recycling centre for environmentally friendly disposal.

SPECIFICATIONS

ARM-880RC

Description	PA zone paging microphone
Transmission method	cable
Gooseneck length	310 mm
Admiss. ambient temp.	0-40 °C
Dimensions	180 × 61 × 143 mm
Weight	1.66 kg
Connection	RJ45
Packaging dimensions (W x H x L)	0.265 x 0.125 x 0.435 m
Gross weight	2.8 kg
Net weight	1.66 kg

ARM-880RC

EAN code	4007754231694
Net weight	1.66 kg