

CDX1-1412/8

Order no.: 1001067

PRODUCT INFORMATION

PA horn driver, 35 W, 8 Ω

- Very compact design for mobile applications
- One-piece polyamide-coated cone and surround
- Recommended crossover frequency: 2,000 Hz (12 dB/oct.)
- 2-hole screw mounting
- Also available as 16 Ω version (CDX1-1412/16)

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Deutschland
info@monacor.com

SPECIFICATIONS

CDX1-1412/8

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	1,500-20,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,000 Hz
Power rating (RMS)	35 W
Peak music power output (MAX)	70 W
SPL	106 dB/W/m
Voice coil diameter	Ø 35 mm
Voice coil material	flat copper-coated aluminium wire
Voice coil former	polyimide
Outlet	Ø 25 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	Ø 52 mm (2x M5)
Dimensions	Ø 60 mm x 34.5 mm
Outside diameter	Ø 60 mm
Width	Ø 60 mm
Height	Ø 60 mm
Depth	34.5 mm
Colour	black/silver
Admiss. ambient temp.	0-40 °C
Weight	0.35 kg
Packing unit	1
Type of speaker	1"
Packaging dimensions (W x H x L)	0.115 x 0.065 x 0.115 m
Gross weight	0.4 kg
Net weight	0.35 kg

CDX1-1412/8

EAN code	0739894646451
Net weight	0.35 kg