

CDX1-1425/8

Order no.: 1001069

PRODUCT INFORMATION

PA horn driver, 25 W, 8 Ω

- High-quality 25 mm (1") compression driver with 35 mm (1.4") voice coil and ferrite magnet
- Aluminium cone with elastomer surround
- Inductance copper coil for an improved RF performance
- Recommended crossover frequency: 2,500 Hz (12 dB/oct.)
- 2-hole screw mounting

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Deutschland
info@monacor.com

SPECIFICATIONS

CDX1-1425/8

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	2,000-20,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,500 Hz
Power rating (RMS)	25 W
Peak music power output (MAX)	50 W
SPL	108 dB/W/m
Voice coil diameter	Ø 35 mm
Voice coil material	flat copper-coated aluminium wire
Outlet	Ø 25 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	Ø 76 mm (2x M6)
Dimensions	Ø 90 mm x 58 mm
Outside diameter	Ø 90 mm
Width	Ø 90 mm
Height	Ø 90 mm
Depth	58 mm
Colour	black/silver
Admiss. ambient temp.	0-40 °C
Weight	0.42 kg
Packing unit	1
Type of speaker	1"
Packaging dimensions (W x H x L)	0.09 x 0.08 x 0.09 m
Gross weight	0.45 kg
Net weight	0.42 kg

CDX1-1425/8

EAN code	0739894534451
Net weight	0.42 kg