

CDX1-1430/8

Order no.: 1001070

PRODUCT INFORMATION

PA horn driver, 50 W, 8 Ω

- 25 mm (1") horn driver
- Standard 2-hole screw mounting
- Neodymium drive system with cooling
- Wide and extra linear frequency response
- Very high sound pressure level with lowest distortions
- From approx. 3,000 Hz already, this driver provides a very high-quality sound in 2-way arrangements, even with 38 cm (15") bass speakers
- Compatible with various horns, including MRH-180

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Deutschland
info@monacor.com

SPECIFICATIONS

CDX1-1430/8

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	20-20,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,500 Hz
Power rating (RMS)	50 W
Peak music power output (MAX)	100 W
SPL	108 dB/W/m
Voice coil diameter	Ø 35 mm
Voice coil material	copper-coated aluminium
Outlet	Ø 25 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	Ø 76 mm (2x M6)
Dimensions	Ø 90 mm x 58 mm
Outside diameter	Ø 90 mm
Width	Ø 90 mm
Height	Ø 90 mm
Depth	58 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	0.47 kg
Packing unit	1
Type of speaker	1"
Packaging dimensions (W x H x L)	0.13 x 0.08 x 0.11 m
Gross weight	0.5 kg
Net weight	0.42 kg

CDX1-1430/8

EAN code	0739894536752

CDX1-1430/8

Net weight	0.42 kg