

CDX1-1720/8

Order no.: 1001071

PRODUCT INFORMATION

PA horn driver, 50 W, 8 Ω

- High-quality 25 mm (1") compression driver with 44 mm (1.75") voice coil and ferrite magnet
- Phase plug wih maximum modal suppression
- Deep-drawn titanium cone with polyimide surround
- Recommended crossover frequency: 1,500 Hz (12 dB/oct.)
- 4-hole screw mounting

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Deutschland
info@monacor.com

SPECIFICATIONS

CDX1-1720/8

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	800-20,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	1,500 Hz
Power rating (RMS)	50 W
Peak music power output (MAX)	100 W
SPL	107 dB/W/m
Voice coil diameter	Ø 44 mm
Voice coil material	flat copper-coated aluminium wire
Outlet	Ø 25 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	Ø 76 mm (4x M6)
Dimensions	Ø 88.5 mm x 55 mm
Outside diameter	Ø 88.5 mm
Width	Ø 88.5 mm
Height	Ø 88.5 mm
Depth	55 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	0.62 kg
Packing unit	1
Type of speaker	1"
Packaging dimensions (W x H x L)	0.1 x 0.075 x 0.13 m
Gross weight	0.72 kg
Net weight	0.62 kg

CDX1-1720/8

EAN code	0739894571357
Net weight	0.62 kg