

CDX1-1747/8

Order no.: 1001078

PRODUCT INFORMATION

PA horn driver, 60 W, 8 Ω

- High-quality 25 mm (1") compression driver with 44 mm (1.75") voice coil and ferrite magnet
- Modern development with Finite Element Analysis (FEA)
- Standard 2-hole and 3-hole screw mounting
- Wideband and highly linear frequency response up to 20,000 Hz
- Very high sound pressure with minimum distortion

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Deutschland
info@monacor.com

SPECIFICATIONS

CDX1-1747/8

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	1,000-20,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	1,600 Hz
Power rating (RMS)	60 W
Peak music power output (MAX)	120 W
SPL	110 dB/W/m
Voice coil diameter	Ø 44 mm
Voice coil material	flat copper-coated aluminium wire
Outlet	25 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	Ø 76 mm (2 x M6), Ø 57.2 mm (3 x M6)
Dimensions	Ø 120 mm x 53 mm
Outside diameter	Ø 120 mm
Width	Ø 120 mm
Height	Ø 120 mm
Depth	53 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	1.96 kg
Packing unit	1
Type of speaker	1"
Packaging dimensions (W x H x L)	0.135 x 0.07 x 0.178 m
Gross weight	2.06 kg
Net weight	1.96 kg

CDX1-1747/8

EAN code	0739894584852

CDX1-1747/8

Net weight	1.96 kg