

CDX14-3030/8

Order no.: 1001080

PRODUCT INFORMATION

PA horn driver, 100 W,8 Ω

- 35 mm (1.4") high-quality compression driver with 75 mm (3") voice coil and ferrite magnet
- One-piece titanium cone and surround
- Recommended crossover frequency: 1,000 Hz (12 dB/oct.)
- 4-hole screw mounting

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen

Deutschland
info@monacor.com

SPECIFICATIONS

CDX14-3030/8

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	500-20,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	1,000 Hz
Power rating (RMS)	100 W
Peak music power output (MAX)	200 W
SPL	106.5 dB/W/m
Voice coil diameter	Ø 75 mm
Voice coil material	flat copper-coated aluminium wire
Outlet	Ø 35 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	Ø 102 mm (4 x M6)
Dimensions	Ø 180 mm x 68 mm
Outside diameter	Ø 180 mm
Width	Ø 180 mm
Height	Ø 180 mm
Depth	68 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	5.5 kg
Packing unit	1
Type of speaker	1.4"
Packaging dimensions (W x H x L)	0.235 x 0.095 x 0.19 m
Gross weight	5.7 kg
Net weight	5.5 kg

CDX14-3030/8

EAN code	0739894589642
Net weight	5.5 kg