

DRIVE-08A

Order no.: 1000192

PRODUCT INFORMATION

With the DRIVE series
you will get robust and easy-to-use PA speakers which are suitable for versatile applications and feature the latest DSP-controlled amplifier technology. There are 3 selectable presets available to provide a perfect sound adjustment for any kind of application. These robust and high-quality cabinets made of birch plywood are suitable for general use. The arrangement of the handles allow for easy manageability.

Professional active DSP speaker system with 2-channel amplifier, 200 W

- Compact 8/2 full range system with cabinet made of birch plywood
- DSP-controlled 2-channel amplifier (bass: class D, tweeter: class A/B)
- 3 selectable presets

- FLAT (linear adjustment)
- MUSIC (slightly raised bass and treble)
- LOW CUT (with high-pass filter for application with an additional subwoofer)

- 20 cm (8") bass speaker and 25 mm (1") horn tweeter, can be turned by 90°
- Excellent sound characteristics

- High-quality coating and neat workmanship
- Multi-purpose positioning and installation options
- Horn tweeter with consistent radiation pattern
- M8 threaded inserts for suspended installation, stand sleeve
- Volume control
- 2 x balanced line in
- 2 x parallel line out
- 1 x balanced mix out
- Power and clip indicator

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices
The appliance is supplied with life-threatening mains voltage. Therefore, never tamper with it yourself and do not insert anything into the ventilation openings. There is a risk of electric shock.
Do not operate the appliance and disconnect the mains plug from the socket immediately if there is visible damage to the appliance or the mains cable, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialist workshop for repair.
Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).
Never set the speaker volume very high. High volumes can damage your hearing in the long term!
Never pull the mains plug out of the socket by the cable, always grasp the plug.
If the appliance is to be taken out of service for good, hand it over to a local recycling centre for environmentally friendly disposal.

SPECIFICATIONS

DRIVE-08A	
Active/passive	active
Transmission technology	cable
Total output power	400 W
Power rating (RMS)	DSP-controlled 200 W (140 + 60) bass: 140 W treble: 60 W
Frequency range	60-20,000 Hz
Input signal	790 mV/40 kΩ (line, bal.)

DRIVE-08A

System	8/2 full range
Bass speaker	20 cm (8") bass speaker
Tweeter	25 mm (1") horn tweeter
Number of speakers	2
Speaker size	20 cm (8")
SPL	98 dB/W/m
Max. rated SPL	122 dB
Radiation angle/beam angle	H: 90°/V: 60°, horn can be turned
Radiation angle, horizontal	90°
Radiation angle, vertical	60°
Housing material	birch plywood
Colour	black
Mounting device	M8 threaded inserts, stand sleeve
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/250 VA
Dimensions	270 x 460 x 290 mm
Width	270 mm
Height	460 mm
Depth	290 mm
Weight	9.4 kg
Inputs	1 x comb. XLR/6.3 mm: line 1 x XLR: line
Outputs	2 x XLR par. out 1 x XLR mix out
Other features	DSP-controlled limiter 3 selectable presets
Packaging dimensions (W x H x L)	0.38 x 0.54 x 0.36 m
Gross weight	12.24 kg
Net weight	9.4 kg

DRIVE-08A

EAN code	4007754276251
Net weight	9.4 kg