

E-7BPSETD/5

Order no.: 0259611

PRODUCT INFORMATION

UHF PLL audio transmission set,
consisting of:

- 2-channel diversity UHF PLL receiver E-7DU/5
- UHF PLL pocket transmitter with lavalier microphone (set of 2) E-7TBD/5

Carrier frequency range: 504-542 MHz
For specifications, please refer to individual items.

There are restrictions or requirements within in the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan

jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries/rechargeable batteries.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

SPECIFICATIONS

E-7BPSETD/5

General information

Description	UHF PLL audio transmission set
Carrier frequency range	506-542 MHz
Audio frequency range	40-18,000 Hz
Channels	2
THD	< 0.6%
Dynamic range	> 100 dB
Operating time	> 30 h
Admiss. ambient temp.	0-40 °C

Specifications transmitter

E-7BPSETD/5

Power supply transmitter	2 x batt. size AA, alkaline (not supplied)

Specifications receiver

Audio signal receiver	180 mV jack
Power supply receiver	via encl. power supply
Width receiver	221 mm
Height receiver	40 mm
Depth receiver	152 mm
Weight receiver	570 g
Connections receiver	1 x 6.3 mm jack, bal.

E-7BPSETD/5

EAN code	4007754273571
Net weight	0.57 kg