

EDL-416EN/WS

Order no.: 0163420

PRODUCT INFORMATION

Moisture-proof PA ball speaker,
with EN 54-24 certification, 1438-CPR-0535.

- 100 V transmission technology
- White ABS housing (UL 94HB), UV-resistant and weatherproof
- Moisture-proof speaker cone
- Supplied with 450 cm connection cable and canopy
- Ceramic connection terminal, thermal fuse

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

EDL-416EN/WS

Active/passive	passive
Transmission technology	100 V
Total power rating	16 W
Power rating (RMS)	16/8/4 W
Frequency range	130-18,000 Hz
System	130 mm full range speaker
Number of speakers	1
Speaker size	13 cm (5")
SPL	89.9 dB/W/m
Max. rated SPL	101 dB
Radiation angle/beam angle	196° (1 kHz)132° (2 kHz)170° (4 kHz)
Radiation angle, horizontal	196° (1 kHz)132° (2 kHz)170° (4 kHz)
Radiation angle, vertical	196° (1 kHz)132° (2 kHz)170° (4 kHz)
Housing material	ABS
Colour	white, RAL 9010
Mounting device	canopy
Protection class	IP35
Admiss. ambient temp.	-20 °C to +80 °C
Dimensions	Ø 185 mm x 157 mm
Width	Ø 185 mm
Height	157 mm
Depth	Ø 185 mm
Weight	1.6 kg
Inputs	ceramic terminal with thermal fuse
Packaging dimensions (W x H x L)	0.19 x 0.18 x 0.19 m
Gross weight	1.79 kg
Net weight	1.64 kg

EDL-416EN/WS

EAN code	4007754254662
Net weight	1.64 kg