

ESP-315/WS

Order no.: 0162870

PRODUCT INFORMATION

2-way PA wall speaker

- 100 V PA speaker with excellent sound quality
- 2-way system with a 10 x 15 cm full-range driver and a 13 mm dome tweeter
- Power taps: 15/10/5/2.5 W
- Power selector switch with 8 Ω operating position
- Can be mounted horizontally or vertically
- Individually adjustable dispersion angle
- White plastic version with white-painted metal grille
- Supplied with wall brackets

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

ESP-315/WS

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	30 W
Power rating (RMS)	15/10/5/2.5 W (100 V)15 W (8 Ω)
Impedance	8 Ω
Frequency range	75-20,000 Hz
System	2-way
Number of speakers	2
Speaker size	10 x 15 cm (4" x 6")
SPL	90 dB/W/m
Radiation angle/beam angle	H: 140°/V: 100°
Radiation angle, horizontal	140°
Radiation angle, vertical	100°
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 133 mm x 280 mm
Width	Ø 133 mm
Height	280 mm
Depth	Ø 133 mm
Weight	2.1 kg
Inputs	spring-load. speaker term.
Packaging dimensions (W x H x L)	0.15 x 0.15 x 0.305 m
Gross weight	2.38 kg
Net weight	2.2 kg

ESP-315/WS

EAN code	4007754222210
Net weight	2.2 kg