

FGA-30M

Order no.: 0213010

PRODUCT INFORMATION

Ground isolator,
compact design, for preventing signal interference and hum loops which may occur, e.g. when connecting PC sound cards or laptops to an amplifier.

- Galvanically isolated inputs and outputs
- 2 RCA plugs
- 3.5 mm stereo jack plug
- Input/output impedance 20 kΩ
- Frequency response 20?30,000 Hz
- Total harmonic distortion < 0.01 %
- Transmission ratio 1:1
- Ø 24 mm x 38 mm, 32 g
- Length including connection cable approx. 11.5 cm

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

FGA-30M	
Description	ground isolator
Frequency range	20-30,000 Hz
Input impedance	20 kΩ
Output impedance	20 kΩ
Transmission ratio	1:1
THD	< 0.01%
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 24 mm x 38 mm
Weight	45 g
Inputs	1 x RCA plug L/R, 1 x 3.5 mm stereo plug
Outputs	1 x RCA plug L/R, 1 x 3.5 mm stereo plug

FGA-30M	
EAN code	4007754227352
Net weight	0.045 kg