

FGM-170

Order no.: 0236070

PRODUCT INFORMATION

Floor stand microphone,
with carbon fibre boom.

- 3 high-quality back electret microphone cartridges with different polar patterns
- Low cut switch (80 Hz)
- 10 dB attentuation, switchable
- Extra lightweight (105 g) but very robust carbon fibre boom (1.46 m) with miniature gooseneck
- Long shaft, for overhead miking
- Structure-borne noise isolated diecast base plate
- Supplied with 2 replacement cartridges, connection cable and windshield
- Delivery consists of 2 boxes

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

FGM-170

Description	microphone floor stand
Transmission method	cable
Polar pattern	cardioid, supercardioid, omnidir.
System	back electret
Audio frequency range	50-18,000 Hz
Nominal impedance	220 Ω
Sensitivity	16 mV/Pa
Max. sound pressure	125 dB
Power supply	DC 12-48 V, phantom power
Admiss. ambient temp.	0-40 °C
Dimensions	1.46 m (boom) 1.6 m (stand)
Weight	3.6 kg
Connection	cable with 3-pole mini XLR to XLR
Packaging dimensions (W x H x L)	0.3 x 0.26 x 1.51 m
Gross weight	4.3 kg
Net weight	3.72 kg

FGM-170

EAN code	4007754224054
Net weight	3.72 kg