FLAT-M200

Order no.: 0259876

PRODUCT INFORMATION

Active PA stage monitor speaker system, 300 W

- Flat and very compact full range system
- Fitted with 4 x 10 cm (FaitalPRO, 4 x 4") full range speaker with neodymium magnets
- Class D amplifier system
- Sound pressure at nominal power: 122 dB
- Indication of signal and limiter
- Volume control and tone control
- Balanced line/mic input and feed-through output
- High-quality multiplex wooden cabinet with protective metal grille
- 2 x M10 and 2 x M6 threaded inserts for stand adapter or mounting device
- Supplied with clamp for mounting, e.g. onto a microphone stand

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices
The appliance is supplied with life-threatening mains voltage. Therefore, never tamper with it yourself and do not insert anything into the ventilation openings. There is a risk of electric shock. Do not operate the appliance and disconnect the mains plug from the socket immediately if there is visible damage to the appliance or the mains cable, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialist workshop for repair. Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).
Never set the speaker volume very high. High volumes can damage your hearing in the long term!
Never pull the mains plug out of the socket by the cable, always grasp the plug.

If the appliance is to be taken out of service for good, hand it over to a local recycling centre for environmentally friendly disposal.

SPECIFICATIONS

FLAT-M200	
Active/passive	active
Transmission technology	cable
Total output power	300 W
Power rating (RMS)	200 W
Frequency range	70-20,000 Hz
Input signal	25 mV/28 kΩ (line, bal.), 6 mV/20 kΩ (mic, bal.)
System	4 x 4", full range
Full range speaker	4 x 10 cm (FaitalPRO 4 x 4") full range speaker
Number of speakers	4
Speaker size	10 cm (4")
SPL	98 dB/W/m
Max. rated SPL	122 dB
Radiation angle/beam angle	H: 50°/V: 70°
Radiation angle, horizontal	50°
Radiation angle, vertical	70°
Housing material	multiplex
Colour	black
Mounting device	2 x M10 threaded insert, 2 x M6 threaded insert
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/356 VA
Dimensions	320 x 150 x 250 mm
Width	320 mm
Height	150 mm
Depth	250 mm
Weight	4.11 kg
Inputs	1 x comb. XLR/6.3 mm (line/mic)
Outputs	1 x XLR link out
Other features	limiter
Accessories	FLAT-M200BAG

FLAT-M200

Packaging dimensions (W x H x L)	0.35 x 0.18 x 0.35 m
Gross weight	4.82 kg
Net weight	4.11 kg

FLAT-M200

EAN code	4007754272536
Net weight	4.11 kg