

GM-5212SW

Order no.: 1000894

PRODUCT INFORMATION

Electret gooseneck microphone with on/off push-button

- Supercardioid polar pattern
- Natural sound, precise voice reproduction
- Low susceptibility to acoustic feedback
- LED for indicating operating status
- Silent on/off push-button
- Reliable and high-quality workmanship for a long service life
- Gooseneck with integrated 3-pole XLR plug
- Operation via external phantom power supply or desktop base
- Supplied with windshield

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

GM-5212SW

Description	gooseneck microphone
Version	LED
Transmission method	cable
Polar pattern	supercardiod
System	back electret
Audio frequency range	80-18,000 Hz
Nominal impedance	100 Ω
Sensitivity	15.8 mV/Pa
S/N ratio	74 dB
Max. sound pressure	125 dB
Power supply	DC 12-48 V phantom power
Gooseneck length	305 mm
Admiss. ambient temp.	0-40 °C
Dimensions	466 mm
Weight	180 g
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.495 x 0.091 x 0.059 m
Gross weight	0.33 kg
Net weight	0.18 kg

GM-5212SW

EAN code	4007754419399
Net weight	0.18 kg