

SMART PHONE FRIENDLY

GML-5218

Order no.: 0234570

PRODUCT INFORMATION

Electret gooseneck microphones with LED

- 3 replaceable microphone cartridges with different polar patterns (cardioid, supercardioid and omnidirectional)
- Excellent speech intelligibility
- -10 dB PAD switch
- Switchable low cut filter
- LED for indicating operating status
- Reliable and high-quality workmanship for a long service life
- Gooseneck with integrated 3-pole XLR plug
- Operation via external phantom power or desktop microphone base DMS-5

Electret microphone, with gooseneck, with 3 replaceable microphone cartridges, with low cut switch, with -10 dB attentuator, with LED for indicating operating status, with 3-pole XLR plug for 3-pole XLR inline jack, frequency rage from 80 Hz to 18 kHz, cardioid/supercardioid/omnidirectional polar pattern, nominal impedance at 1 kHz: 220 ohms, phantom power: 48 V DC, length: 615 mm.

Manufacturer information:
JTS PROFESSIONAL CO., LTD.

No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

GML-5218

Description	gooseneck microphone
Version	LED
Transmission method	cable
Polar pattern	cardioid/supercardioid/omnidir.
System	back electret
Audio frequency range	80-18,000 Hz
Nominal impedance	220 Ω ± 30%
Sensitivity	16 mV/Pa
Max. sound pressure	125 dB
Power supply	DC 48 V phantom power
Admiss. ambient temp.	0-40 °C
Dimensions	615 mm
Weight	245 g
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.09 x 0.06 x 0.655 m
Gross weight	0.465 kg
Net weight	0.245 kg

GML-5218

EAN code	4007754194524
Net weight	0.245 kg