

IMC-300T/VA

Order no.: 1000998

PRODUCT INFORMATION

With this 360° pendant speaker, it is possible to implement a relatively large-scale PA application. When installed at a mounting height of 4 m, you are able to provide a homogeneous sound radiation for approx. 200 m^2. The speaker features an excellent sound quality due to the 2-way coaxial speaker system with a large housing.

High-quality 2-way PA pendant speaker,
with perfect 360° sound radiation and EN 54-24 certification.

- 100 V transmission technology: 30/20/10 W
- 2-way coaxial speaker (6.5")
- Elaborate reflector design for a wide and homogeneous omnidirectional radiation
- Excellent sound reproduction due to the attached housing, even down to the bass
- Recommended intallation height: approx. 4 m (reflector)
- White lacquered sheet steel housing
- Suspension via steel safety ropes and snap hooks
- Cable inlet via high-strength cable gland (PG11)
- Ceramic terminal

SPECIFICATIONS

IMC-300T/VA

Active/passive	passive
Transmission technology	100 V
Total power rating	30 W
Power rating (RMS)	30/20/10 W
Frequency range	60-20,000 Hz
Bass speaker	1
Tweeter	1
Number of speakers	2
Speaker size	16 cm (6.5")
SPL	83 dB/W/m
Max. rated SPL	98 dB
Radiation angle/beam angle	H: 360°/V: 160°
Radiation angle, horizontal	360°
Radiation angle, vertical	160°
Housing material	metal
Colour	white
Mounting device	steel rope with snap hook
Protection class	IP54
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 480 mm x 300 mm
Width	Ø 480 mm
Height	300 mm
Depth	Ø 480 mm
Weight	4.5 kg
Inputs	1 x high-strength cable gland (PG11)
Other features	EN 54
Accessories	supplied with safety rope for suspended installation
Packaging dimensions (W x H x L)	0.57 x 0.36 x 0.57 m
Gross weight	7.66 kg
Net weight	5 kg

IMC-300T/VA

EAN code	4007754422764
Net weight	5 kg