LMS-808

Order no.: 0202160

PRODUCT INFORMATION

Microphone line mixer/line splitter

- Multifunctional device with three selectable operating modes:

- Mixer operation for mixing up to 8 mono input signals (6 x line/mic and 2 x line) to 1 stereo ouptut
- Line splitter operation for splitting 2 mono line inputs to 6 mono outputs
- Level matching amplifier operation for boosting up to 6 input signals

- 6 mono input channels, each with switchable 12 V phantom power, pan pot, signal/clip LED and individual selection of the operating mode
- 2 mono line input channels, each with level control and signal/clip LED

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

LMS-808	
No. of channels	8
No. of inputs	8
Mic input	1 mV/6.6 kΩ (mic), 6 x XLR, bal.
Line input	250 mV/30 kΩ, 2 x XLR , bal. 100 mV/40 kΩ, 6 x XLR, bal.
Master output	1 V/200 Ω, 6 x XLR, bal. (mono), 1 x XLR L/R, bal. (stereo)
Frequency range	10-30,000 Hz
THD	0.02%
S/N ratio	81 dB, weighted
Crosstalk	-63 dB
Power supply	˜ 230 V/50 Hz/10 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	10 VA
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 48 x 200 mm, 1 RU
Width	482 mm
Height	48 mm
Depth	200 mm
Rack units, RU	1
Weight	2.9 kg
Packaging dimensions (W x H x L)	0.25 x 0.09 x 0.535 m
Gross weight	3.88 kg
Net weight	3.14 kg

LMS-808	
EAN code	4007754182026
Net weight	3.14 kg