LS-280/SW

Order no.: 0202220

PRODUCT INFORMATION

8-way line splitter

- 2 separate inputs
- Selectable operating modes:

- 1. input A to 4 outputs,
- input B to 4 outputs
- 2. input A to 8 outputs

- XLR connection and gain control for each input and output
- Dual LED for indicating signal and peak for the inputs

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal

which is not harmful to the environment.

SPECIFICATIONS

LS-280/SW

Description	splitter
Frequency range	20-20,000 Hz
Input signal	100 mV
Input impedance	15 kΩ
Output signal	1 V
Output impedance	100 Ω
S/N ratio	70 dB, unweighted
THD	< 0.03%
Admiss. ambient temp.	0-40 °C
Power supply	˜ 230 V/50 Hz/10 VA
Dimensions	482 x 48 x 205 mm, 1 RU
Weight	2.3 kg
Inputs	2 x XLR
Outputs	8 x XLR

LS-280/SW

EAN code	4007754182699
Net weight	2.34 kg