LSP-102

Order no.: 0251680

PRODUCT INFORMATION

2-channel 3-way line splitter,
(2 inputs/6 outputs), e.g. for connecting one mixer to several amplifiers.

- 1 balanced XLR input (600 Ω) for each channel
- 2 galvanically isolated, balanced XLR outputs (600 Ω) with ground lift switch for each channel
- 1 balanced XLR direct output for each channel
- Frequency range: 20-20,000 Hz
- Robust metal housing with very good shielding qualities, suitable for stage applications
- Dimensions: 160 x 55 x 105 mm
- Weight: 909 g

SOUNDCHECK 07/2007
on the FGA-102, FGA-202, LC-31, MC-31 and LSP-102:
“Every musician or sound engineer should have these little helpers in their toolbox. They impress by their unobtrusiveness. Both the robust metal housing and the functionality of these transformers allow to solve many problems on stage or in the studio at a reasonable price.”

tools4music 06/2009
on the LSP-102, LC-31, FGA-102, FGA-202, DIB-102
“Recommendable and fit for on-the-road applications. An attractively priced little audio aid, perfect for the 'ever accompanying' tool case.”

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

LSP-102

Description	splitter
Frequency range	20-20,000 Hz
Input impedance	600 Ω
Output impedance	600 Ω
Admiss. ambient temp.	0-40 °C
Dimensions	160 x 55 x 105 mm
Weight	909 g
Inputs	2 x XLR, bal.
Outputs	6 x XLR, bal.
Other features	ground lift switch

LSP-102

EAN code	4007754197730
Net weight	0.909 kg