MEQ-115/SW

Order no.: 0244350

PRODUCT INFORMATION

Graphic equalizer

- 2-channel version, 2 x 15 frequency controls in 2/3 octave steps
- Switchable control range ±6/±12 dB
- Peak LED
- Switchable low cut filter
- Master volume control
- Bypass switch and ground lift switch
- Frequency controls with centre click
- Inputs and outputs each via 2 x XLR and 2 x 6.3 mm jack

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

MEQ-115/SW

Description	graphic equalizer
Frequency range	20-20,000 Hz
Control range	switchable ±6/±12 dB
Control frequencies	2 x 25/40/63/100/160/250/400/630 Hz/ 1/1.6/2.5/4/6.3/10/16 kHz
Input signal	0.775 V
Input impedance	50 kΩ
Output signal	0.775 V
Output impedance	600 Ω
Low cut	20 Hz/-3 dB
S/N ratio	66 dB
THD	< 0.1%
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/10 VA
Dimensions	482 x 44.5 x 165 mm, 1 RU
Weight	2.5 kg
Inputs	2 x XLR, 2 x 6.3 mm jack
Outputs	2 x XLR, 2 x 6.3 mm jack

MEQ-115/SW

EAN code	4007754185218
Net weight	2.52 kg