

MKA-50SET/WS

Order no.: 0132360

PRODUCT INFORMATION

Active 2-way stereo speaker systems, 2 x 20 W

- Set consists of an active and a passive speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Active speaker system with integrated 2-channel amplifier and power supply
- Speakers with magnetic shielding
- Auto-standby function
- Volume control and 2-way tone control

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices
The appliance is supplied with life-threatening mains voltage. Therefore, never tamper with it yourself and do not insert anything into the ventilation openings. There is a risk of electric shock. Do not operate the appliance and disconnect the mains plug from the socket immediately if there

is visible damage to the appliance or the mains cable, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialist workshop for repair.
Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).
Never set the speaker volume very high. High volumes can damage your hearing in the long term!
Never pull the mains plug out of the socket by the cable, always grasp the plug.
If the appliance is to be taken out of service for good, hand it over to a local recycling centre for environmentally friendly disposal.

SPECIFICATIONS

MKA-50SET/WS	
Active/passive	active/passive
Transmission technology	cable
Total output power	2 x 40 W
Power rating (RMS)	2 x 20 W
Frequency range	60-20,000 Hz
Input signal	420 mV/24 kΩ
System	2-way
Bass speaker	13 cm (5") bass-midrange speaker
Tweeter	2.5 cm (1") tweeter
Number of speakers	2
Speaker size	13 cm (5")
SPL	89 dB/W/m
Max. rated SPL	102 dB
Radiation angle/beam angle	H: 120°/V: 100°
Radiation angle, horizontal	120°
Radiation angle, vertical	100°
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/110 VA
Dimensions	180 x 250 x 160 mm
Width	180 mm
Height	250 mm
Depth	160 mm
Weight	5.9 kg (pair)

MKA-50SET/WS

Inputs	1 x RCA L/R (active speaker system only) 1 x 3.5 mm jack screw twerminals (both speaker systems)
Packaging dimensions (W x H x L)	0.21 x 0.27 x 0.435 m
Gross weight	6.42 kg
Net weight	5.92 kg

MKA-50SET/WS

EAN code	4007754241914
Net weight	5.92 kg