MPX-20USB

Order no.: 0202860

PRODUCT INFORMATION

3-channel stereo DJ mixer,
with USB port. Plug and mix!

- Integrated USB audio interface (will be identified and addressed as an external sound card)
- Full-duplex USB port (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC as well as for recording mixings onto a PC
- 1 microphone input channel
- 2 stereo input channels, switchable line/phono and USB/line/phono
- 1 stereo output channel (master)
- 1 stereo record output
- Pre-fader listening (CUE) to the stereo input channels via adjustable headphone output
- Crossfader
- LED level display
- Robust metal housing of compact size
- Power supply via USB port or optional power supply with USB port

tools4music 04/2015
“Robust design, neat workmanship and great test results. The features of this unit certainly meet the requirements of practical applications.”

delamar.de 11/2014

“The MPX-20USB from IMG Stage Line is a respectable mixer for two channels plus microphone which combines all the important features at a compact size. Great for DJs who concentrate on the essentials. Also suitable for anyone requiring a reliable second unit ... As a little bonus, there are in fact two headphone jacks. This space-saving mixer is able to crossfade two audio signals and well suited for home applications.”

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen

Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

MPX-20USB	
No. of channels	4
No. of inputs	5
Mic input	1 mV, 1 x 6.3 mm jack
Line input	450 mV, 2 x RCA L/R
Phono input	9 mV, 2 x RCA L/R
Master output	1 V, 1 x RCA L/R
Record output	1 V, 1 x RCA L/R
Headphones	≥ 8 Ω, 1 x 3.5 mm jack,1 x 6.3 mm jack
USB	yes
Frequency range	20-20,000 Hz
THD	0.1%
S/N ratio	63 dB, unweighted
Crossfader	yes
Power supply	DC 5 V/500 mAvia USB interface
Operating voltage (possible alternative)	DC 5 V
Power supply (possible alternative)	DC 500 mA
Admiss. ambient temp.	0-40 °C
Dimensions	150 x 70 x 140 mm
Width	150 mm

MPX-20USB

Height	70 mm
Depth	140 mm
Weight	700 g
Packaging dimensions (W x H x L)	0.18 x 0.1 x 0.245 m
Gross weight	0.937 kg
Net weight	0.725 kg

MPX-20USB

EAN code	4007754238853
Net weight	0.725 kg