

NAC3FXXA-W-S

Order no.: 1001052

PRODUCT INFORMATION

NEUTRIK POWERCON plug

- Complies with safety requirements of IEC EN 60320-1, VDE-certified
- For mains connection up to ˜ 250 V/16 A
- Versions for mains input
- Connections for ground, phase and neutral conductor
- Robust version with latching device, all-insulated contacts and cable inlet with self-adjusting clamps
- Self-extinguishing according to UL 94V-0

Manufacturer information:
Neutrik AG
Im alten Ried 143
9494 Schaan
Liechtenstein
neutrik@neutrikgroup.com

SPECIFICATIONS

NAC3FXXA-W-S

Description	plug, input
Type	PowerCon, input
Quantity	1
Features	latching device
Colour/colour coding	black/blue
Power rating	˜ 250 V/16 A
Insulating resistance	10 GΩ
Certification	UL, cUL, VDE
Pole number	3
Cable inlet	Ø 6-12 mm
Connection	screwed contact
Strain relief	yes
Material	silver-plated copper contacts, plastic
Admiss. ambient temp.	-33-+80 °C
Diameter	Ø 26.5 mm
Length	79-82.5 mm
Weight	35 g

NAC3FXXA-W-S

EAN code	7613187017759
Net weight	0.035 kg