

NX-8S

Order no.: 0234780

PRODUCT INFORMATION

Dynamic vocal microphone

- Accentuated and clear voice reproduction
- Wide dynamic range
- Low-noise reed switch resistant to wear
- Significantly reduced transmission of the handling noise
- Non-slip and durable due to special stove-enamel finish
- High-quality and solid workmanship
- Supplied with microphone holder and padded bag

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG

Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

NX-8S

Description	vocal microphone
Transmission method	cable
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-16,500 Hz
Nominal impedance	600 Ω
Sensitivity	2.5 mV/Pa
Max. sound pressure	138 dB
Housing material	diecast metal
Admiss. ambient temp.	0-40 °C
Weight	245 g
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.13 x 0.08 x 0.26 m
Gross weight	0.635 kg
Net weight	0.42 kg

NX-8S

EAN code	4007754194173
Net weight	0.42 kg