

OMNI-TRACK/WS

Order no.: 1000605

PRODUCT INFORMATION

Spottune OMNI TRACK speaker:
wireless 360° speaker for application and mounting to 3-phase high-voltage rail lighting systems, installation via a global track adapter.
Instead of being optimised for a frontal listening position as it is the case with standard speakers, the Spottune OMNI TRACK speaker is acoustically designed to provide a homogeneous radiation. The 360° sound radiation is recommended for environments which require a homogeneous sound radiation to create a consistent listening experience throughout the room. This results in an enhanced listening comfort and a consistent, room-filling sound experience.
Compared with standard speaker systems, you also require less speakers for the installation of a speaker system in a PA application, thanks to 360° sound radiation. The Spottune OMNI TRACK speakers are controlled and managed via radio link, using the Spottune network audio streamer STREAM. One Spottune network audio streamer STREAM is required for each Spottune speaker system which consists of up to 30+ Spottune speakers. Please order this separately.
The easy installation and configuration as well as the possibility to easily adapt the Spottune speaker system to changing requirements and spatial conditions, make the system the ideal partner for use in commercial areas such as retail trade, restaurants and bars, hotels, offices, etc.
Supplied with the GA 69 global track adapter for mounting on a 3-phase high-voltage rail.

Spottune OMNI TRACK speaker

- All-in-one smart speaker (built-in amplifier, audio filter and receiver)

- Easy plug-and-play installation to existing 3-phase rail lighting systems
- Automatic linking and settings in pairing mode with LED status indication at initial operation via Spottune network audio streamer STREAM
- Consistent 360° sound radiation for a constantly pleasant sound experience, independent of the position in the room
- Well-balanced and clear sound at low volume
- Reliable and stable audio transmission in the frequency range of 1.9 GHz
- Closed full range speaker system

Supplied w/o lighting rails.

Manufacturer information:
Spottune ApS
Nordre Fasanvej 113, 2. Floor
2000 Frederiksberg
Denmark
support@spottune.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never adjust the speakers to a very high volume. Permanent high volumes may damage your hearing!
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

OMNI-TRACK/WS	
Active/passive	active
Transmission technology	wireless
Total output power	70 W
Power rating (RMS)	50 W, class D amplifier
Frequency range	50-15,000 Hz
Number of speakers	1
Speaker size	10 cm (4")
Max. rated SPL	100 dB
Radiation angle/beam angle	all-round radiation, 360°
Radiation angle, horizontal	360°
Radiation angle, vertical	360°
Housing material	plastic

OMNI-TRACK/WS

Colour	white
Mounting device	global track adapter GA 69
Admiss. ambient temp.	0-40 °C
Power supply	˜ 100-240 V/50-60 Hz/2 VA max. via 3-phase high-voltage rail
Dimensions	Ø 115 x 200 mm
Width	Ø 115 mm
Height	200 mm
Depth	Ø 115 mm
Weight	1.5 kg
Inputs	conductor rail
Other features	audio transmission: UHF band 1.8-1.9 GHz, operating range: approx. 50-100 m, depending on the surrounding and range of application
Packaging dimensions (W x H x L)	0.175 x 0.335 x 0.175 m
Gross weight	1.9 kg
Net weight	1.5 kg

OMNI-TRACK/WS

EAN code	5700002178404
Net weight	1.5 kg