

PA-1480

Order no.: 0171110

PRODUCT INFORMATION

Mono PA power amplifier

- 1 x 480 W
- Switchable 400 Hz high-pass filter 6 dB/oct.
- Temperature-controlled fan, continuously adjustable
- LED indication for clip, protect, overtemperature and output level
- Feed-through output (link)
- Mains operation or 24 V emergency power operation

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
During operation, there may be a hazard of contact with a dangerous voltage of up to 100 V at the speaker terminals. Always switch off the amplifier before making or changing any connections.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
The heat generated inside the unit must be dissipated by air circulation; never cover the air vents of the housing.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

PA-1480	
Peak output power	480 W
Power rating	480 W
Power rating at 8 Ω	480 W
Power rating at 100 V	480 W
Power rating at 70 V	480 W
Output impedance	62 V/8 Ω, 70 V/10 Ω, 100 V/21 Ω
Channels	1
Inputs	1.2 V, bal.
Frequency range	35-20,000 Hz
S/N ratio	> 100 dB(A)
THD	< 1%
Power supply	˜ 230 V/50 Hz/1,400 VA, DC 24 V/40 A
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,400 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 40 A
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	88 mm
Depth	374 mm
Rack units, RU	2
Weight	15.2 kg
Connections	XLR/screw contacts (inputs) screw contacts (speakers)
Packaging dimensions (W x H x L)	0.54 x 0.18 x 0.48 m

PA-1480

Gross weight	17.24 kg
Net weight	15.22 kg

PA-1480

EAN code	4007754159653
Net weight	15.22 kg