

PA-4000RC

Order no.: 0236010

PRODUCT INFORMATION

PA 4-zone paging desktop microphone,
for connection to PA-40120 and PA-6040MPX.

- Selection buttons for 4 zones, for activating one or several zones
- ALL CALL button for activating all of the 4 zones
- Autom. chime via microphone announcement button (talk)
- LED status indication for the zone buttons (busy, emergency), power, mic fault, signal and talk
- Built-in gooseneck electret microphone
- Adjustable microphone sensitivity
- Chime can be activated or deactivated as required
- 24 V power supply via PA-40120 or PA-6040MPX
- Two RJ45 jacks for connection to PA-40120, PA-6040MPX or optional power supply and additional microphones PA-4000RC
- Supplied with connection module for PA-40120 and PA-6040MPX
- Up to 32 x PA-4000RC can be connected to PA-40120 or PA-6040MPX via bus
- Supplied with 3 m connection cable (Cat. 5e)

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Germany
info@monacor.com

Safety and warning notices
Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).
Do not operate the appliance if there is visible damage to the appliance, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialised workshop for repair.
If the appliance is to be taken out of service permanently, hand it over to a local recycling centre for environmentally friendly disposal.

SPECIFICATIONS

PA-4000RC	
Description	PA desktop microphone
Transmission method	cable
Polar pattern	omnidirectional
Power supply	via PA-40120, PA-6040MPX or optional 24 V power supply
Admiss. ambient temp.	0-40 °C
Weight	0.9 kg
Cable	Cat. 5e, 3 m
Connection	2 x RJ45
Packaging dimensions (W x H x L)	0.16 x 0.18 x 0.375 m
Gross weight	1.202 kg
Net weight	0.9 kg

PA-4000RC	
EAN code	4007754218442
Net weight	0.9 kg