

# PDM-3

Order no.: 0234850

## PRODUCT INFORMATION

**Dynamic vocal microphone**

- Frequency response especially optimised for the vocal spectrum
- Low handling noise and high acoustic feedback suppression
- Robust design for a long life
- Supplied with connection cable

**Manufacturer information:**
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

**EU-Representative:**

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany

info@monacor.com

## SPECIFICATIONS

**PDM-3**

| | |
|---|---|
| Description | vocal microphone |
| Transmission method | cable |
| Polar pattern | cardioid |
| System | dynamic |
| Audio frequency range | 50-16,500 Hz |
| Nominal impedance | 600 Ω |
| Sensitivity | 1.8 mV/Pa |
| Max. sound pressure | 147 dB |
| Housing material | diecast metal |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 315 g |
| Cable | XLR, bal.,XLR, bal. |
| Connection | XLR, bal. |
| Packaging dimensions (W x H x L) | 0.12 x 0.08 x 0.255 m |
| Gross weight | 0.755 kg |
| Net weight | 0.6 kg |

**PDM-3**

| | |
|---|---|
| EAN code | 4007754194258 |
| Net weight | 0.6 kg |