


RDA10

Order no.: 1001171

PRODUCT INFORMATION

Active 2-way flush-mount ceiling speaker,

with integrated Dante® module.

- Full range coaxial ceiling speaker
- Equipped with standard flex terminals
- Frameless construction and slim design
- Removable magnetic, lacquered grille for seamlessly covering the entire speaker
- Supports PoE/PoE+ Ethernet audio connection and power supply via RJ45 connection
- Output power: 10 W (PoE), 20 W (PoE+)
- Compatible with all Dante®/AES67 audio network products
- Transmission of data signals via RJ45 port
- Supports Relacart speaker management software for easy setup and remote management

System requirements Dante®: Windows 7/8.1/10/11 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd

Please note: RELACART products are distributed by MONACOR INTERNATIONAL exclusively in the following countries: Germany, Austria, Switzerland, Netherlands, Belgium, Luxembourg, Denmark, Portugal, Malta. Orders from other countries cannot be fulfilled.

Manufacturer information:
Relacart Electronics Co., Ltd.
1408 Room, B Building
Fengxing Plaza
No. 242, Tianhe Road
Tianhe District
Guangzhou, Guangdong
China
info@relacart.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never adjust the speakers to a very high volume. Permanent high volumes may damage your hearing!
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

RDA10	
Active/passive	active
Transmission technology	Dante®
Total output power	30 W
Power rating (RMS)	10 W (PoE), 20 W (PoE+)
Frequency range	85-17,000 Hz
Input signal	Dante®
System	2-way
Bass speaker	1 x 16 cm

RDA10

Tweeter	1 x 2.5 cm
Number of speakers	1
Speaker size	16 cm (6")
SPL	90 dB/W/m
Max. rated SPL	103 dB
Radiation angle/beam angle	90°
Radiation angle, horizontal	90°
Radiation angle, vertical	90°
Housing material	plastic frame, protective metal grille
Colour	white
Mounting device	ceiling suspension
Power supply	37-57 V PoE/PoE+ via RJ45
Dimensions	Ø 210 mm x 150 mm
Width	Ø 210 mm
Height	Ø 210 mm
Depth	150 mm
Weight	1.5 kg
Inputs	RJ45
Other features	integr. DSP for tone control via software
Packaging dimensions (W x H x L)	0.232 x 0.178 x 0.232 m
Gross weight	1.89 kg
Net weight	1.5 kg

RDA10

EAN code	4007754426694
Net weight	1.5 kg