

RU-901G3/5

Order no.: 0259844

PRODUCT INFORMATION

True diversity UHF PLL wideband receiver

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Removable antennas (BNC connection)
- Auto-scan
- Pilot tone squelch and noise mute
- LED for indicating RF level and AF level
- Backlit display with status indications, e.g. group/channel, frequency, battery, antenna A/B
- XLR output (bal.) and 6.3 mm jack output (unbal.)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

Manufacturer information:
JTS PROFESSIONAL CO., LTD.

No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

RU-901G3/5

General information

Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	50-18,000 Hz
Channels	1
THD	< 0.6%
Dynamic range	105 dB
Admiss. ambient temp.	0-40 °C

Specifications receiver

Audio signal receiver	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 320 mV/600 Ω jack
Power supply receiver	via encl. power supply

RU-901G3/5

Width receiver	212 mm
Height receiver	38 mm
Depth receiver	144 mm
Weight receiver	1.02 kg
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.

RU-901G3/5

EAN code	4007754268638
Net weight	1.26 kg