

SIEM-111/5

Order no.: 0255510

PRODUCT INFORMATION

MPX stereo UHF PLL in-ear monitoring system

- Wireless monitor system with excellent sound characteristics
- Individual monitor mix in stereo mode or mono/mix mode
- For live acts, e.g. theatre performances, musical performances
- 64 preset channels in 4 groups of 16 channels each
- 961 frequencies
- Up to 14 wireless monitor ways can be used for an intermodulation-free parallel operation
- Pilot tone technology and noise squelch
- Transmitter and receiver with lock function, multifunctional display and limiter
- Earphones or headphones can be connected to the transmitter via 3.5 mm or 6.3 mm stereo jack
- Supplied with high-quality in-ear earphones IE-1
- 482 mm (19") rack installation with supplied mounting brackets

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries/rechargeable batteries.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

SPECIFICATIONS

SIEM-111/5	
General information	
Description	in-ear monitoring system
Carrier frequency range	518-542 MHz
Audio frequency range	50-15,000 Hz
Channels	2
Operating time	> 8 h

SIEM-111/5

Admiss. ambient temp.	0-40 °C
Total weight	2.33 kg

Specifications transmitter

Transmitting power	10 mW
Power supply transmitter	˜ 100-240 V via integrated switch-mode power supply
Width transmitter	212 mm
Height transmitter	44 mm
Depth transmitter	239 mm
Weight transmitter	1.3 kg
Connections transmitter	2 x combo input,2 x loop output, bal. via6.3 mm jack

Specifications receiver

Power supply receiver	2 x batt. AA size, alkaline (not supplied)
Width receiver	74 mm
Height receiver	196 mm
Depth receiver	34 mm
Weight receiver	300 g
Connections receiver	3.5 mm stereo jack

SIEM-111/5

EAN code	4007754239416
Net weight	2.33 kg