

SL-250WS/EN

Order no.: 1001158

PRODUCT INFORMATION

Weatherproof PA speaker system with 30 cm (12") coaxial horn speaker,
developed for outdoor applications, with an excellent sound quality. The SL-250WS/EN is ideally suited for applications at versatile locations, e.g. airports, megastores and stadiums.

Weatherproof PA speaker system, 250 W,
with EN 54-24 certification.

- 100 V transmission technology or 8 Ω operation
- 2-way bass-reflex system
- 30 cm (12") coaxial speaker with tweeter and crossover network
- Excellent sound
- IP66 tested
- ABS cabinet with metal grille
- Recessed connection terminal with cover plate and high-strength cable gland
- Supplied with safety rope
- Stainless steel wall bracket

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

SL-250WS/EN	
Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	250 W
Power rating (RMS)	250/125/63 W
Impedance	8 Ω
Frequency range	85-19,000 Hz
System	2-way coaxial
Bass speaker	30 cm (12")
Tweeter	tweeter
Number of speakers	2
Speaker size	30 cm (12")
SPL	99.6 dB/W/m
Max. rated SPL	122.5 dB
Radiation angle/beam angle	130°/135° (500 Hz) 60°/60° (1 kHz) 55°/55° (2 kHz) 85°/60° (4 kHz)
Radiation angle, horizontal	130° (500 Hz) 60° (1 kHz) 55° (2 kHz) 85° (4 kHz)
Radiation angle, vertical	135° (500 Hz) 60° (1 kHz) 55° (2 kHz) 60° (4 kHz)
Housing material	ABS
Colour	white (RAL 9016)
Mounting device	mounting bracket
Protection class	IP66
Admiss. ambient temp.	-25 °C to +70 °C
Dimensions	425 x 418 x 390 mm
Width	425 mm
Height	418 mm
Depth	390 mm
Weight	19.7 kg
Inputs	screw terminal
Packaging dimensions (W x H x L)	0.52 x 0.44 x 0.54 m

SL-250WS/EN

Gross weight	23.5 kg
Net weight	19.7 kg

SL-250WS/EN

EAN code	4007754425871
Net weight	19.7 kg