

TG-10STX/1

Order no.: 0173730

PRODUCT INFORMATION

16-channel PLL Tour Guide System, 863-865 MHz

- With extensive accessories
- Operating range: up to 60 m
- Parallel operation of up to three wireless transmitters
- Licence-free in the EU

16-channel PLL wireless transmitter

- 2 inputs (CH1/CH2) via rear comb. jacks, with level controls
- 1 input (CH3) via 6.3 mm mono jack
- Continuously adjustable headphone output
- 2 loop outputs
- Phantom power can be activated as required

Licence-free in the EU.

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.

41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

TG-10STX/1

General information

Description	tour guide system wireless transmitter
Carrier frequency range	863-865 MHz
Audio frequency range	40-15,000 Hz
Channels	2
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Operating range	60 m
Power supply transmitter	via encl. power supply
Width transmitter	214 mm
Height transmitter	45 mm
Depth transmitter	240 mm
Weight transmitter	1.3 kg

TG-10STX/1

Connections transmitter	2 x comb. jack (input CH1/CH2), 1 x 6.3 mm mono jack (input CH3), 1 x 3.5 mm stereo jack (headphones), 2 x 6.3 mm mono jack (loop outputs)

TG-10STX/1

EAN code	4007754229424
Net weight	1.415 kg