

TG-98TA/5

Order no.: 0257410

PRODUCT INFORMATION

Professional PLL Tour Guide System

- Bandwidth: 36 MHz
- 6 groups with up to 22 channels
- 124 channels
- 506-542 MHz
- Operating range: up to 200 m
- Operating time: approx. 10 hours
- There are restrictions or requirements within the EU!

Professional PLL pocket transmitter

- Built-in electret microphone
- 3.5 mm microphone connection
- Supplied with matching electret tie clip microphone
- Audio input via 3.5 mm jack
- LCD for indicating channel/group, RF, mute and battery status
- Lock function
- Mute function
- Volume level control
- Selectable transmitting power

- Belt clip and lanyard
- Parallel operation possible of up to 22 transmitters max.
- Connection cable 801TG with 3.5 mm plug is available at option for certain JTS headband microphones

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

SPECIFICATIONS

TG-98TA/5	
General information	
Description	tour guide system pocket transmitter
Carrier frequency range	506-542 MHz
Audio frequency range	40-18,000 Hz

TG-98TA/5

Channels	1
Operating time	> 10 h
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Operating range	200 m
Power supply transmitter	2 x 1.2 V NiMH rech. batt. AA size (not supplied)
Width transmitter	62 mm
Height transmitter	112 mm
Depth transmitter	28 mm
Weight transmitter	72 g
Connections transmitter	1 x 3.5 mm jack (microphone), 1 x 3.5 mm jack (audio input)

TG-98TA/5

EAN code	4007754248944
Net weight	0.150 kg