

TK-600

Order no.: 0234890

PRODUCT INFORMATION

Dynamic vocal microphone

- Impressive vocal microphone, also meets high requirements, available at an attractive price
- Powerful and brilliant sound reproduction
- Minimised handling noise
- Low susceptibility to acoustic feedback
- Mechanical stability
- Low-noise reed switch resistant to wear
- Supplied with connection cable

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG

Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

TK-600

Description	vocal microphone
Transmission method	cable
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-16,000 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	147 dB
Housing material	diecast metal
Admiss. ambient temp.	0-40 °C
Weight	380 g
Cable	XLR, bal.
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.13 x 0.075 x 0.26 m
Gross weight	0.78 kg
Net weight	0.63 kg

TK-600

EAN code	4007754194302
Net weight	0.63 kg