

TR-3-4

Order no.: 1001476

PRODUCT INFORMATION

Compact weatherproof horn speaker, 4 Ω,
for speech and alarm applications

- Very high sound pressure (100 dB/1 W/1 m)
- IP69k certified, suitable for use in trains, fire engines and call stations
- Light grey PC/ABS housing (self-extinguishing, complies with UL94V0 standard)
- Connection via 2-core cable (length 0.6 m)
- Mounting bracket included

Manufacturer information:
PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

SPECIFICATIONS

TR-3-4

Active/passive	passive
Transmission technology	cable
Power rating (RMS)	10 W
Impedance	4 Ω
Frequency range	250-20,000 Hz
Number of speakers	1
SPL	100 dB/W/m
Max. rated SPL	109 dB
Radiation angle/beam angle	150°
Radiation angle, horizontal	150°
Radiation angle, vertical	150°
Housing material	PC/ABS
Colour	light grey, RAL 7035
Mounting device	mounting bracket
Protection class	IP69K
Admiss. ambient temp.	-40 °C to +110 °C
Dimensions	Ø 97 mm x 102 mm
Width	Ø 97 mm
Height	Ø 97 mm
Depth	102 mm
Weight	0.5 kg
Inputs	cable connection
Other features	weatherproof
Packaging dimensions (W x H x L)	0.14 x 0.14 x 0.1 m
Gross weight	0.6 kg
Net weight	0.5 kg

TR-3-4

EAN code	4007754430097
Net weight	0.5 kg