

TR-3

Order no.: 1001475

PRODUCT INFORMATION

Compact pressure chamber loudspeaker
for voice and alarm applications

- 100 volt transmission technology
- 100 V transformer with power taps on the 6/3/1.5 W cable
- Very high characteristic sound pressure (100 dB/1 W/1 m)
- IP69k-tested, suitable for use in trains, fire engines and call stations
- Light grey PC/ABS housing (self-extinguishing, complies with UL94V0 standard)
- Connection via 4-core cable (length 0.6 m)
- Mounting bracket included

Manufacturer information:
PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

SPECIFICATIONS

TR-3

Active/passive	passive
Transmission technology	100 V
Total power rating	6 W
Power rating (RMS)	6/3/1.5 W
Frequency range	250-20,000 Hz
Number of speakers	1
SPL	100 dB/W/m
Max. rated SPL	107 dB
Radiation angle/beam angle	150°
Radiation angle, horizontal	150°
Radiation angle, vertical	150°
Housing material	PC/ABS
Colour	Light grey, RAL 7035
Mounting device	Mounting bracket
Protection class	IP69K
Admiss. ambient temp.	-40 °C to +110 °C
Dimensions	Ø 97 mm x 102 mm
Width	Ø 97 mm
Height	Ø 97 mm
Depth	102 mm
Weight	0.6 kg
Inputs	Cable connection
Other features	weatherproof
Packaging dimensions (W x H x L)	0.14 x 0.14 x 0.1 m
Gross weight	0.7 kg
Net weight	0.6 kg

TR-3

EAN code	4007754430080
Net weight	0.6 kg