

TS-C50-1000/T

Order no.: 0163470

PRODUCT INFORMATION

Weatherproof PA column speaker,
with EN 54-24 certification.

- 100 V transmission technology
- 8 x 7.7 cm (3") waterproof full range speaker
- 4 power taps: 50/30/15/7.5 W
- Connection via ceramic terminals with thermal fuse in the cabinet
- 2 x PG9 cable gland
- Robust, plastic-coated aluminium cabinet with front protective grille
- The speaker complies with British Standard BS 5839, part 8
- Supplied with plastic wall bracket for pivoting and tilting

Manufacturer information
ic audio GmbH
Boehringerstr. 14a
68307 Mannheim
Germany
info@ic-audio.com

SPECIFICATIONS

TS-C50-1000/T

Active/passive	passive
Transmission technology	100 V
Total power rating	50 W
Power rating (RMS)	50/30/15/7.5 W
Frequency range	200-20,000 Hz
Full range speaker	8 x 77 mm
Number of speakers	8
Speaker size	7.5 cm (3")
SPL	100 dB/W/m
Max. rated SPL	117 dB
Radiation angle/beam angle	H173°/V17°
Radiation angle, horizontal	173°
Radiation angle, vertical	17°
Housing material	aluminium
Colour	white aluminium, RAL 9006
Mounting device	wall bracket
Protection class	IP66
Admiss. ambient temp.	-20 °C to +90 °C
Dimensions	100 x 971 x 92 mm
Width	100 mm
Height	971 mm
Depth	92 mm
Weight	5.1 kg
Inputs	ceramic screw terminals
Packaging dimensions (W x H x L)	0.18 x 0.19 x 1.05 m
Gross weight	5.83 kg
Net weight	5.21 kg

TS-C50-1000/T

EAN code	4007754258172
Net weight	5.21 kg