

UF-20TB/5

Order no.: 0257230

PRODUCT INFORMATION

The wideband multifrequency system UF-20... from JTS
is the perfect solution for stage applications of high requirements due to an excellent flexibility and reliability.
The device impresses with a convenient setup function, REMOSET technology, 75 MHz bandwidth, 3,000 frequencies which can be selected as desired and additional professional features, e.g. active carrier analysis method.

UHF PLL pocket transmitter

- Suitable for combination with a headband microphone or an instrument microphone with 4-pole mini XLR connector
- Bandwidth: 75 MHz
- 15 groups, each with up to 63 compatible preset channels
- 64 channels in 6 groups from 3,000 selectable individual frequencies can be stored in user presets
- REMOSET technology for receiver/transmitter synchronisation
- Adjustable sensitivity (-18 dB to +12 dB)
- Lock function
- 5-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

tools4music 06/2015
“With the wireless system UF-20, JTS is able to offer an absolutely professional system. Despite numerous features, the menu navigation can easily be followed and understood. The REMOSET function allows you to simultaneously adjust up to 48 transmitters and receivers. In addition, important functions of the hand-held transmitter can remotely be controlled via the receiver which is particularly helpful at festivals. It allows you to quickly adjust the microphone sensitivity. The system also impresses with an appealing design and a neat workmanship.”

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

SPECIFICATIONS

UF-20TB/5

General information

UF-20TB/5

Description	pocket transmitter
Carrier frequency range	530-605 MHz
Audio frequency range	50-18,000 Hz
Channels	1
Operating time	> 20 h
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	10/50 mW
Power supply transmitter	2 x batt. AA size (not supplied)
Width transmitter	62 mm
Height transmitter	170 mm
Depth transmitter	23 mm
Weight transmitter	90 g
Connections transmitter	4-pole mini XLR

UF-20TB/5

EAN code	4007754246834
Net weight	0.565 kg