

WALL-08T/WS

Order no.: 1000608

PRODUCT INFORMATION

Pair of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white
- 4 power taps as well as switchable to 8 Ω operation
- 20 cm (8") bass-midrange speaker and 25 mm (1") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

WALL-08T/WS

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	120 W
Power rating (RMS)	50/25/12.5/6.25 W (100 V) 60 W (8 Ω)
Impedance	8 Ω
Frequency range	35-20,000 Hz
System	2-way
Bass speaker	20 cm (8") bass-midrange speaker
Tweeter	25 mm (1") dome tweeter
Number of speakers	2
Speaker size	20 cm (8")
SPL	90 dB/W/m
Max. rated SPL	106 dB
Radiation angle/beam angle	H: 100°/V: 80°
Radiation angle, horizontal	100°
Radiation angle, vertical	80°
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Protection class	IP65
Admiss. ambient temp.	0-40 °C
Dimensions	245 x 378 x 306 mm (with bracket)
Width	245 mm
Height	378 mm
Depth	306 mm
Weight	5 kg
Inputs	spring-loaded speaker terminal
Other features	for pivoting and tilting
Packaging dimensions (W x H x L)	0.29 x 0.41 x 0.59 m
Gross weight	11.8 kg
Net weight	10.54 kg

WALL-08T/WS

EAN code	4007754410907
Net weight	10.54 kg