

# WDR-130-10

Order no.: 1001433

## PRODUCT INFORMATION

**PA ceiling speaker**

- 100 V transmission technology
- Speaker (13 cm) with high sound pressure and very good transmission range
- Moisture-proof speaker cone
- Quick-mounting device
- Metal housing with metal protective grille
- 3 power taps via pressure clamps
- Ball-proof according to DIN 18 032, part 3

**Manufacturer information:**
PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

# SPECIFICATIONS

**WDR-130-10**

| | |
|---|---|
| Transmission technology | 100 V |
| Frequency range | 70-19,000 Hz |
| Power rating (RMS) | 10/5/2.5 W |
| SPL | 93 dB/W/m |
| Max. rated SPL | 103 dB |
| Radiation angle, horizontal | 180° |
| Radiation angle, vertical | 180° |
| Mounting cutout | Ø 140-150 mm |
| Dimensions | Ø 167 mm x 62 mm |
| Outside diameter | Ø 167 mm |
| Width | Ø 167 mm |
| Height | Ø 167 mm |
| Depth | 62 mm |
| Colour | white, RAL 9010 |
| Protective class | IP54 |
| Weight | 0.95 kg |
| Packing unit | 1 |
| Type of speaker | 130 |
| Packaging dimensions (W x H x L) | 0.187 x 0.187 x 0.075 m |
| Gross weight | 1 kg |
| Net weight | 0.9 kg |

**WDR-130-10**

| | |
|---|---|
| EAN code | 4007754429671 |
| Net weight | 0.9 kg |