

WDR-245-CX30

Order no.: 1001497

PRODUCT INFORMATION

PA ceiling speaker

- 100 V transmission technology
- 2-way speaker system (20 cm)
- High sound quality and balanced frequency response, distortion-free transmission of 60 Hz signals is also possible
- Quick-mounting device
- Metal housing with metal protective grille
- 3 power taps via pressure clamps
- Ball-proof in accordance with DIN 18 032, part 3

Manufacturer information:
PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

SPECIFICATIONS

WDR-245-CX30

Transmission technology	100 V
Frequency range	60-20,000 Hz
Power rating (RMS)	30/15/7.5 W
SPL	95 dB/W/m
Max. rated SPL	110 dB
Radiation angle, horizontal	160°
Radiation angle, vertical	160°
Mounting cutout	Ø 215-230 mm
Dimensions	Ø 252 mm x 120 mm
Outside diameter	Ø 252 mm
Width	Ø 252 mm
Height	Ø 252 mm
Depth	120 mm
Colour	white, RAL 9010
Weight	2.5 kg
Packing unit	1
Type of speaker	200
Packaging dimensions (W x H x L)	0.27 x 0.27 x 0.115 m
Gross weight	2.6 kg
Net weight	2.5 kg

WDR-245-CX30

EAN code	4007754430301
Net weight	2.5 kg