

WDR-245-N

Order no.: 1001439

PRODUCT INFORMATION

PA ceiling speaker, 4 Ω

- 100 V transmission technology through audio transformer with 3 power taps
- High-performance full-range speaker (20 cm) with very high characteristic sound pressure (98 dB/1 W/1 m)
- Quick-mounting device
- Metal housing with metal protective grille
- Connection via pressure clamp
- Ball-proof in accordance with DIN 18 032, Part 3

Manufacturer information:
PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

SPECIFICATIONS

WDR-245-N

Impedance (Z)	4 Ω
Transmission technology	cable
Frequency range	50-18,000 Hz
Power rating (RMS)	15 W
SPL	98 dB/W/m
Max. rated SPL	109 dB
Radiation angle, horizontal	150°
Radiation angle, vertical	150°
Mounting cutout	Ø 215-230 mm
Dimensions	Ø 252 mm x 82 mm
Outside diameter	Ø 252 mm
Width	Ø 252 mm
Height	Ø 252 mm
Depth	82 mm
Colour	white, RAL 9010
Weight	1.1 kg
Packing unit	1
Type of speaker	200
Packaging dimensions (W x H x L)	0.27 x 0.27 x 0.115 m
Gross weight	1.3 kg
Net weight	1.2 kg

WDR-245-N

EAN code	4007754429732
Net weight	1.2 kg