

WDW-330-EN-10

Order no.: 1001421

PRODUCT INFORMATION

PA wall speaker
with EN 54-24 certification

- 100 V transmission technology through audio transformer with 3 power taps
- Full-range speaker (13 cm) with good sound quality and speech intelligibility
- Design plastic housing (ventilated) with metal protective grille
- Horizontal and vertical mounting options thanks to symmetrical design
- Supplied with mounting screws and screw head covers

Manufacturer information:
PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

SPECIFICATIONS

WDW-330-EN-10

Active/passive	passive
Transmission technology	100 V
Total power rating	10 W
Power rating (RMS)	10/5/2,5 W
Frequency range	80-19,000 Hz
Number of speakers	1
Speaker size	13 cm (5")
SPL	93 dB (1 W/1 m) 76 dB (EN, 1 W/4 m)
Max. rated SPL	103 dB (1 m) 88 dB (EN, 4 m)
Radiation angle/beam angle	H180°/V180° (500 Hz) H180°/V180° (1 kHz) H180°/V1115° (2 kHz) H51°/V68° (4 kHz)
Radiation angle, horizontal	180° (500 Hz) 180° (1 kHz) 180° (2 kHz) 51° (4 kHz)
Radiation angle, vertical	180° (500 Hz) 180° (1 kHz) 115° (2 kHz) 68° (4 kHz)
Features	EN 54-24 certification
Housing material	ABS
Colour	White, RAL 9010
Mounting device	Mounting screws
Protection class	IP54
Dimensions	330 x 240 x 83 mm
Width	330 mm
Height	240 mm
Depth	83 mm
Weight	1.6 kg
Inputs	WAGO terminal block
Packaging dimensions (W x H x L)	0.343 x 0.24 x 0.89 m
Gross weight	1.7 kg
Net weight	1.6 kg

WDW-330-EN-10

EAN code	4007754429565
Net weight	1.6 kg