



CM-22G12W

Order No.: 0233940

Price upon request

PRODUCTINFOS

Overhead hanging condenser microphone

- For suspended installations, especially suitable for applications in which a direct microphonic effect is undesired for optical or operational reasons, e.g. sound pickup of choirs or on theatre stages or school stages
- High-quality condenser microphone cartridge with 1.25 cm (½") extra thin gold-plated diaphragm, cardioid polar pattern
- Low cut switch (80 Hz)
- 10 dB attenuation, switchable
- Integrated phantom power supply adapter
- Flexible alignment due to gooseneck
- Black (CM-22G...B) or white (CM-22G...W) version
- Supplied with windshield

Total length:

CM-22G6...: 205 mm

CM-22G12...: 340 mm

TECHNICAL SPECIFICATIONS

CM-22G12W

Description	overhead hanging microphone
Transmission method	cable
Polar pattern	cardioid
System	condenser
Audio frequency range	20-20,000 Hz
Nominal impedance	100 Ω
Sensitivity	15.8 mV/Pa
Max. sound pressure	140 dB
Power supply	DC 48 V, phantom power
Housing material	metal
Admiss. ambient temp.	0-40 °C
Weight	160 g
Cable	8 m
Connection	XLR, bal.
Packing dimensions (W x H x L)	0.095 x 0.065 x 0.38 m
Gross weight	0.47 kg
Net weight	0.34 kg