



EDL-620EN

Order No.: 0163180

Price upon request

PRODUCTINFOS

PA ceiling speakers,

with EN 54-24 certification.

- 100 V line technique with 3 power taps
- Full range speaker with optimised voice reproduction
- Plastic cover with low mounting depth
- For a ceiling thickness from 5 to 22 mm
- Quick installation
- Robust metal basket and protective grille

TECHNICAL SPECIFICATIONS

EDL-620EN

| | |
|---------------------|---------------|
| Transmission method | 100 V |
| Frequency range | 120-15,000 Hz |
| Power rating (RMS) | 20/10/5 W |

EDL-620EN

| | |
|--------------------------------|-----------------------|
| Sensitivity | 93 dB/W/m |
| Mounting cutout | Ø 180 mm |
| Mounting depth | 60 mm |
| Dimensions | Ø 200 mm x 70 mm |
| Outside diameter | Ø 200 mm |
| Width | Ø 200 mm |
| Depth | 70 mm |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 1.1 kg |
| Packing unit | 1 |
| Type of speaker | 165 |
| Packing dimensions (W x H x L) | 0.245 x 0.1 x 0.245 m |
| Gross weight | 1.346 kg |
| Net weight | 1.104 kg |