



ESP-5U

Order No.: 0162160

Price upon request

PRODUCTINFOS

PA wall and ceiling speaker for flush mounting

- 100 V line technique via audio transformer with 3 power taps
- Wide bandwidth radiation for a pleasant music reproduction
- 13 cm speaker of high efficiency (94 dB/W/m)
- Plastic tray for flush mounting in walls or solid ceilings
- Required hole in wall: approx. 242 x 242 x 100 mm
- Metal front grille with plastic frame

TECHNICAL SPECIFICATIONS

ESP-5U

| | |
|---------------------|---------------|
| Transmission method | 100 V |
| Frequency range | 100-19,000 Hz |
| Power rating (RMS) | 6/3/1.5 W |
| Sensitivity | 94 dB/W/m |
| Mounting cutout | 242 x 242 mm |

ESP-5U

| | |
|--------------------------------|------------------------|
| Mounting depth | 100 mm |
| Dimensions | 248 x 248 x 100 mm |
| Width | 248 mm |
| Height | 248 mm |
| Depth | 100 mm |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 1.4 kg |
| Packing unit | 1 |
| Type of speaker | 130 |
| Packing dimensions (W x H x L) | 0.255 x 0.12 x 0.255 m |
| Gross weight | 1.578 kg |
| Net weight | 1.403 kg |