



EUL-26/WS

Order No.: 0163290

Price upon request

PRODUCTINFOS

Pairs of miniature PA speaker systems

- Speakers for general applications, very small dimensions, 100 V line technique
- Can also be connected at 8 Ω
- 6.5 cm (2.5") full range speaker
- Good sound characteristics and speech intelligibility
- Turnable, wall bracket with ball joint allows for pivoting and tilting
- An additional subwoofer system is recommended for complementing the low-frequency music reproduction (e.g. EUL-2SUB/SW, SOUND-100SUB)

TECHNICAL SPECIFICATIONS

EUL-26/WS

Active/passive	passive
Transmission method	100 V
Total power rating	20 W

EUL-26/WS

Power rating (RMS)	6 W (100 V) 10 W (8 Ω)
Impedance	8 Ω
Frequency range	150-20,000 Hz
Number of speakers	1
Speaker size	6.5 cm (2.5")
Sensitivity	88 dB/W/m
Colour	white
Mounting device	wall bracket
Admiss. ambient temp.	0-40 °C
Dimensions	90 x 90 x 115 mm
Width	90 mm
Height	90 mm
Depth	115 mm
Weight	0.65 kg
Inputs	spring-load. speaker term.
Other features	pair
Packing dimensions (W x H x L)	0.11 x 0.11 x 0.295 m
Gross weight	1.436 kg
Net weight	1.306 kg