



EUL-80/SW

Order No.: 0161190

Price upon request

PRODUCTINFOS

Pair of universal PA speaker systems

- 100 V line technique, 2-way version
- EUL-80... with a 25 mm dome tweeter, EUL-60... and EUL-30... with an 11 mm dome tweeter
- Excellent sound quality
- 6-step power selector switch
- Black (SW) or white (WS) plastic cabinet
- Pivoting mounting bracket
- Bevelled shape of cabinets also allows mounting in corners

TECHNICAL SPECIFICATIONS

EUL-80/SW

Active/passive	passive
Transmission method	100 V
Power rating (RMS)	30/15/7.5/4/2 W
Frequency range	40-20,000 Hz

EUL-80/SW

System	bass-reflex
Sensitivity	89 dB/W/m
Max. rated SPL	103 dB
Housing material	plastic
Colour	black
Mounting device	movable mounting bracket
Admiss. ambient temp.	0-40 °C
Dimensions	270 x 370 x 220 mm
Width	270 mm
Height	370 mm
Depth	220 mm
Weight	5.4 kg
Inputs	spring-load. speaker term.
Packing dimensions (W x H x L)	0.34 x 0.44 x 0.55 m
Gross weight	14.66 kg
Net weight	12.72 kg